
IZOELEKTRO

Note: How to enable 3-D content in .pdf viewer






Izoelektro d.o.o.
www.izoelektro.com

Limbuška cesta 2
2341 Limbuš
Slovenia, EU

tel: +386 2 66 22 500
fax: +386 2 66 22 505
info@izoelektro.com

IZOELEKTRO

MV surge arrester SNO-RP DH 40,8 kV + Connectors AA
Code: 0012000740002



Technical information

U_c	40,8	kV	Continuous operating voltage
U_r	51	kV	Rated voltage
U_{res}	125,56	kV	Residual voltage
AD	409	mm	Arcing distance
CD	1234	mm	Creepage distance
A	450	mm	Minimum distance to wall
B	470	mm	Minimum distance between phases
H	391	mm	Surge arrester height
N	11		Number of Sheds

General data

I_n	10	kA	Nominal discharge current
$I_{4/10}$	100	kA	High impulse current
I_{sc}	20	kA	Short circuit current
I_Ω	≤ 0,1	mA	Leakage current
Q_{rs}	≥ 0,4	C	Repetitive charge transfer rating
Q_{th}	≥ 1,1	C	Thermal charge transfer rating
M_{SSL}	250	Nm	Cantilever strength
T	-60 +85	°C	Ambient temperature range
Coat	silicone		Arrester housing
Colour	grey		Silicone colour
Class	DH		Arrester Class
IEC	IEC 60099-4; 60099-5		

Competitive advantages

- *surge arresters for indoor and outdoor installation,*
- *a certificate from an accredited laboratory CESI - Italy,*
- ***varistors directly encased by silicone,***
- *a rigid housing construction,*
- *low residual voltage,*
- *high energy absorbtion,*
- *a maintenance-free operation,*
- ***100% routine tests with a robot and engraved result mark.***

At the customer's request we produce and deliver surge arresters:

- *as a factory set by buyer's choice,*
- *with desired creeping distance,*
- *with continuous operating voltage U_c from 1 to 44kV.*


Izoelektro d.o.o.
www.izoelektro.com

Limbuška cesta 2
2341 Limbuš
Slovenia, EU

tel: +386 2 66 22 500
fax: +386 2 66 22 505
info@izoelektro.com

IZOELEKTRO

MV connector AA



Note: All dimensions are in millimetres

Purpose: connector for top or bottom

Pos.	Pcs.	Name	Standard	Material
1	2	Screw M12x25	DIN 933, ISO 4017	A2
2	2	Flat washer M12	DIN 125 A, ISO 7089	A2
3	2	Spring washer M12	DIN 127 B	A2

Izoelektro d.o.o.
www.izoelektro.com

Limbuška cesta 2
2341 Limbuš
Slovenia, EU

tel: +386 2 66 22 500
fax: +386 2 66 22 505
info@izoelektro.com